

LED-Segment light fixture "SuperNova"

includes Control box and Power Supply

The light fixture "SuperNova" consists of 8 LED-Segments, controller (8-chanel-dimmer, analog) plus connecting cable.

The individual segments swivel from -45 degrees to plus 100 degrees by means of adjustment thumbscrews (shown in picture 1).

Each individual segment is dimmable by its own rotary potentiometer. A master potentiometer controls the light intensity of all 8 segments.

Because of the swivel mechanism It is possible to use the light fixture vertically or horizontally once the proper holding fixture it used.

The holding Fixture is an option and must be ordered.

Technical Data:

Approx inner diameter of light fixture:140 mm (5 33/64 inch)

Color temperature:5700K

Weight:2kg (4,409 lb.)

Actual luminous flux of a LED Aegment:500 lm

Light intensity at middle of the light fixture:.....approx. 2.9 Mlux **Efficiency:**......117 lm/Watt

(The color measurement was carried out according to the CIE D65 standard, see test report)

Chose version here:

SuperNova + Steuergerät + Netzteil 1.249,50 € VAT included SuperNova + Steuergerät + Netzteil+Halter 1.368,50 € VAT included

Telefon:

Fax:

E-Mail:

Web:

WEEE-Reg. Nr.: DE41890637

+49 7247 947066

+49 7247 947067

info@stonemaster.eu http://www.stonemaster.eu

Subject to changes without notice

For customers outside EU countries: Quotations have to be obtained